



*The worldwide leader
in high quality horizontal
aluminum blinds.*



Key Features

Offering maximum strength and sleek styling, our H2 blinds give the traditional look of 2" slats and can be optimized for a range of design applications. The H200 model features heavy-duty slats of .008" gauge aluminum and a low-profile steel headrail measuring 1-1/2" x 2-1/4" x .024" for maximum strength. The H200 provides superior light control with 42mm tape spacing and offers a wide selection of ladder tapes in vinyl, polyester, or fabric.

- heat-treated, spring-tempered aluminum slats bounce back instead of bending, delivering best-in-class durability
- clutch tilter prevents over-rotation of slats, prolonging the life of each blind
- closed oval steel bottom rail provides optimal strength to prevent bowing
- Hunter Douglas blinds are an environmentally responsible choice, with 70% to 95% recycled aluminum content
- backed by our lifetime limited warranty

Find full specifications and samples on all products at www.hunterdouglascontract.com/windowcoverings. Or call us at **800-727-8953** for additional information.

HunterDouglasContract

WINDOW COVERINGS

12400 Stowe Drive
Poway, CA 92064
www.hunterdouglascontract.com

Customer Service: 800.727.8953
Fax: 800.205.9819
Sales: 800.964.2580



Additional colors may be available by arrangement. Ask us for more information.

* Note: when ordering, please specify color #, color name

Product Specifications

PART 2 - PRODUCTS

2.01 ACCEPTABLE MANUFACTURER

A. Hunter Douglas Contract / 12400 Stowe Drive/ Poway, CA 92064 / Phone: 800-727-8953 Fax: 800-205-9819 /Website: www.hunterdouglascontract.com/windowcoverings, or architect approved equivalent.

B. Product substitutions must be approved by architect minimum of 30 days prior to close of bid.

2.02 2" HORIZONTAL ALUMINUM BLINDS

A. PRODUCT: Hunter Douglas "H200 2" Aluminum Blind"

B. MATERIALS:

1. SLATS: 2" wide x .008" thick prior to painting, heat-treated and spring tempered (except 5000 series alloy on metallized finishes) aluminum alloy 6011 with eased corners and manufacturing burrs removed. Furnish not less than nominal 7.2 slats per foot to ensure tight closure and light control. Finish with manufacturer's standard baked-on finish in colors selected by architect from manufacturer's available contract colors utilizing Dust Shield™ finish to inhibit dust build-up for easier maintenance.

2. SLAT SUPPORT: Braided ladders of 100% polyester yarn color compatible with slats and spacing of ladder no more than 42mm.

3. HEADRAIL: U-shaped profile with rolled edges, measuring 1 1/2" x 2 1/4" x .024" constructed of corrosion resistant steel. Internally fit with components required for specified performance and designed for smooth, quiet, trouble-free operation. Headrail finish to be standard baked-on polyester and to match slats. Ends fitted with zinc coated steel end lock with adjustable tab for centering blinds.

4. BOTTOM RAIL: .019" steel, with corrosion-resistant finish formed with double-lock seam into closed oval shape for optimum beam and torsional strength. Ends fitted with color-coordinated engineered polymer caps. Color-coordinated engineered polymer tape buttons secure the ladder and cord. Bottom Rail finish to be standard baked-on polyester color coordinated to slats.

5. LIFTING MECHANISM: Crashproof steel cordlocks with corrosion-resistant finish and steel locking dogs, polyester cord which meet or exceed commercial specifications No/ 1029-86 lift cords, and Break-Thru® safety tassel. Located on either side of individual blind unit as per architect's request.

6. TILTING MECHANISM: Die-cast helical worm and gear type tilter gear mechanism in polymer housing with clutch action to protect ladder tapes from over rotation of the solid steel, corrosion resistant tilt rod.

7. TILT CONTROL WAND: Tubular shaped 7/16" diameter

extruded clear plastic, ribbed for positive grip and detachable without tools. Located on either side of individual blind unit as per architect's request.

8. MOUNTING HARDWARE: Manufacturer's standard .030" steel box brackets with baked-on polyester finish to match headrail with additional support brackets for blinds over 84" wide.

9. ADDITIONAL AVAILABLE OPTIONS: Cord Tilt, Ring Pulls, Valance, Hold Down Brackets, 2 or 3 Blinds on 1 Headrail, Cutouts.

2.03 FABRICATION

A. Blind measurements shall be accurate to within ± 1/8" or as recommended in writing by manufacturer.

2.04 FINISHES

A. SLAT finish selection from the following: 002 Alabaster, 018 Satin Silver, 064 Bronze, 065 Brushed Aluminum, 110 Gloss White, 125 Bright White, 174 Eggshell, 186 Beige, 190 Bright Aluminum, 206 Fawn, 267 White Blush, 269 Chenille, 270 Linen, 350 Vanilla, 413 Hunter Green, 748 Shadow Gray, 830 Almond, 837 Rosewood, 840 Azure, 885 Flex White, 973 Antique White, 974 Pearl.

B. SLAT SUPPORT braided ladders shall be color coordinated with slat.